



# Commercial Units

Specification	36000btu
Rating Cooling / Heating Power (W)	65
Rating Cooling / Heating Current (A)	0.3
EER	3.11
Air Circulation (m <sup>3</sup> /h)	1500/1200/1050
Dimensions Indoor (mm)	1280 x 660 x 205
Packaging Dimensions Indoor (mm)	1346 x 710 x 280
Weight (kg) Indoor (net / gross)	33 / 38
Applicable Room Area (m <sup>3</sup> )	40 -100
Noise Level DB (A)	= 50/47/41



<b>Specification</b>	<b>48000btu</b>
Rating Cooling / Heating Power (W)	105
Rating Cooling / Heating Current (A)	0.48
EER	2.73
Air Circulation (m <sup>3</sup> /h)	1800/1440/1260
Dimensions Indoor (mm)	1631 x 660 x 205
Packaging Dimensions Indoor (mm)	1697 x 710 x 280
Weight (kg) Indoor (net / gross)	44 / 49
Applicable Room Area (m <sup>2</sup> )	60 -140
Noise Level DB (A)	= 51/48/42



<b>Specification</b>	<b>60000btu</b>
Rating Cooling / Heating Power (W)	105
Rating Cooling / Heating Current (A)	0.48
EER	2.81
Air Circulation (m <sup>3</sup> /h)	1800/1440/1260
Dimensions Indoor (mm)	1631 x 660 x 205
Packaging Dimensions Indoor (mm)	1697 x 710 x 280
Weight (kg) Indoor (net / gross)	44 / 49
Applicable Room Area (m <sup>3</sup> )	80 - 180
Noise Level DB (A)	= 51/48/42