



Split Units

Specification	9000btu
Rating Cooling / Heating Power (W)	950 / 980
Rating Cooling / Heating Current (A)	4.21 / 4.35
EER	2.76
Air Circulation (m ³ /h)	420
Dimensions Indoor (mm)	745 x 250 x 210
Dimensions Outdoor (mm)	760 x 260 x 540
Packaging Dimensions Indoor (mm)	810 x 320 x 280
Packaging Dimensions Outdoor (mm)	880 x 370 x 605
Weight (kg) Indoor (net / gross)	9.5 / 11
Weight (kg) Outdoor (net / gross)	30 / 33
Applicable Room Area (m ³)	12 - 20
Noise Level DB (A)	= 37 / 50



Specification	12000btu
Rating Cooling / Heating Power (W)	1220 / 1320
Rating Cooling / Heating Current (A)	5.8 / 6.1
EER	2.88
Air Circulation (m ³ /h)	520
Dimensions Indoor (mm)	745 x 250 x 210
Dimensions Outdoor (mm)	760 x 260 x 540
Packaging Dimensions Indoor (mm)	810 x 320 x 280
Packaging Dimensions Outdoor (mm)	880 x 370 x 605
Weight (kg) Indoor (net / gross)	9.5 / 11
Weight (kg) Outdoor (net / gross)	36 / 39
Applicable Room Area (m ²)	16 - 24
Noise Level DB (A)	= 41 / 51



Specification	18000btu
Rating Cooling / Heating Power (W)	1910 / 2050
Rating Cooling / Heating Current (A)	9.5 / 9.4
EER	2.76
Air Circulation (m ³ /h)	850
Dimensions Indoor (mm)	1095 x 312 x 205
Dimensions Outdoor (mm)	800 x 300 x 590
Packaging Dimensions Indoor (mm)	1175 x 375 x 270
Packaging Dimensions Outdoor (mm)	940 x 420 x 650
Weight (kg) Indoor (net / gross)	15 / 17
Weight (kg) Outdoor (net / gross)	42 / 45
Applicable Room Area (m ³)	26 - 36
Noise Level DB (A)	= 46 / 53



Specification	24000btu
Rating Cooling / Heating Power (W)	2700 / 2700
Rating Cooling / Heating Current (A)	12.5 / 12.5
EER	2.61
Air Circulation (m ³ /h)	1000
Dimensions Indoor (mm)	1095 x 312 x 205
Dimensions Outdoor (mm)	800 x 300 x 690
Packaging Dimensions Indoor (mm)	1175 x 375 x 270
Packaging Dimensions Outdoor (mm)	940 x 420 x 750
Weight (kg) Indoor (net / gross)	115 / 17
Weight (kg) Outdoor (net / gross)	51 / 55
Applicable Room Area (m ³)	35 - 47
Noise Level DB (A)	= 49 / 55



Specification	30000btu
Rating Cooling / Heating Power (W)	3400 / 3500
Rating Cooling / Heating Current (A)	15.1 / 15.5
EER	2.59 / 2.68
Air Circulation (m ³ /h)	1300
Dimensions Indoor (mm)	1310 x 322 x 240
Dimensions Outdoor (mm)	902 x 332 x 795
Packaging Dimensions Indoor (mm)	1420 x 440 x 380
Packaging Dimensions Outdoor (mm)	1030 x 420 x 850
Weight (kg) Indoor (net / gross)	20 / 23
Weight (kg) Outdoor (net / gross)	65 / 77
Applicable Room Area (m ³)	50 - 68
Noise Level DB (A)	= 55 / 56